



## Blue Shield Grade 3560



### Reinforced Asphalt Laminated Paper

**Product Description:** Blue Shield Grade 3560 is a high strength all-purpose waterproof laminated paper.

**Composition:** Grade 3560 is a combination of 2 sheets natural kraft paper laminated with 60 lbs/3MSF of asphalt. 3560 is reinforced with a tri-directional pattern of fiberglass.

**Sizes & Weight:** Blue Shield Grade 3560 is offered in the following widths and lengths:

Widths: 24", 36", 48", 60", 72", 96"

Lengths: 300' and 600'

\*\*\* Custom sizing is available, contact Holland for more information\*\*\*

Grade 3560 weighs approximately 42 lbs per MSF (thousand square feet).

**Applicable Standards:** Exceeds Federal Specification UU-B-790a, Type 1, Grade B, Style 1a.

- **ASTM D-779** – Standard Test Method For Water Resistance of Paper, Paperboard and Other Sheet Material by the Dry Indicator Method.
- **ASTM D-828** – Tensile Properties of Paper and Paperboard Using Constant-Rate of Elongation Apparatus
- **ASTM E-96** – Water Vapor Transmission of Materials

### Superior Protection

Blue Shield Grade 3560 has the ingredients to excel where other products may fail. Much like the other papers in Holland's Blue Shield lineup, 3560 provides tremendous moisture protection while adding an element of strength and durability. The double layer of fiberglass reinforcement provides excellent tear resistance and helps to create a product ideal for construction and building applications as well as heavy duty industrial packaging.

3560 is highly suitable for concrete curing by controlling the hydration period and thereby reducing premature cracking. 3560 aids in the proper curing period that is essential for the strength and eventual life of concrete.

### Applications

- Export Shipment Protection
- Machine Part Wrap
- General Metal Wrap
- Floor Liner for trucks or rail cars
- High Strength moisture barrier wrapping paper
- Concrete Curing paper



**Holland Manufacturing Co, Inc.**

Succasunna, NJ – Corporate HQ  
Attleboro, MA – Polyfiber Mfg Facility  
973-584-8141  
www.hollandmfg.com