



## **Blue Shield Grade RPW**



### **Reinforced Poly-Coated Paper**

**Product Description:** Reinforced Poly Wrap (RPW) is a poly-coated, reinforced kraft paper.

**Composition:** Reinforced Poly Wrap is high strength 50lb/3MSF natural kraft coated with 1 mil of extruded white polyethylene with tri-directional fiberglass reinforcing threads.

**Sizes & Weight:** Blue Shield Grade RPW is offered in the following widths and lengths:

Widths: 24", 36", 48", 60", 72", 96"

Lengths: 300' and 600'

\*\*\* Custom sizing is available, contact Holland for more information\*\*\*

Grade RPW weighs approximately 22 lbs per MSF (thousand square feet).

**Reinforced Poly Wrap Features:**

- Oil, grease and water resistant barrier
- Reinforced for tear and puncture resistance
- Good MVTR (Moisture Vapor Transfer Rate)
- Non-bleed, non-staining

### **Enhanced Durability**

Reinforced Poly Wrap (RPW) is a commonly used wrapping material in the metal industry offering both moisture and tear resistance. The fiberglass scrim pattern resists tear propagation and the white PE coating provided barrier as well as a printable surface.

The most common applications for RPW are light to medium duty wrapping of metal products. If more tear resistance is required, Holland also recommends looking at GPW and SW-40 grades which have increased durability.

### **Applications**

- Metal Packaging
- Machine Part Wrap
- Lumber Wrap
- Floor Liner for trucks or rail cars
- High Strength moisture barrier wrapping paper



**Holland Manufacturing Co, Inc.**

Succasunna, NJ – Corporate HQ  
Attleboro, MA – Polyfiber Mfg Facility  
973-584-8141  
[www.hollandmfg.com](http://www.hollandmfg.com)