



# HI-TECH

## Product Specification

### H-40

### H-40

#### Description

H-40 is a medium duty grade, reinforced water activated tape. H-40 is available in the metric widths shown below. The product is available in natural and white.

#### Construction

##### Papers

Top Sheet: 23 lbs/ream Natural or 30# lbs/ream White High Strength Virgin Kraft  
Bottom Sheet: 23 lbs/ream MG Natural High Strength Virgin Kraft

##### Laminating Adhesive

Non-Asphaltic Polypropylene based polymer  
Non-Staining, Flexible, Water Resistant, Complies with FDA; CFR 175.105

##### Reinforcement

3-Way Fiberglass Reinforcing Pattern  
**Pattern:** Lengthwise threads with diamond cross-machine pattern  
**Lengthwise Threads:** G75 Fiberglass – (1-1-1-1-1) at 1/2" spacing per 72mm  
**Cross-Machine Threads:** G150 Fiberglass – Diamond Pattern 1/4" spacing between threads

##### Adhesive

Smooth, even coating of special high tack, water-activated, modified corn starch based adhesive

##### Caliper

5.9 to 6.9 mils

#### Performance

Tensile Data*	Machine Direction*	Cross Machine Direction*
H-40	55-60 lbs/in	22-27 lbs/in
H-40 White	55-60 lbs/in	24-29 lbs/in

\*Nominal values shown.

#### Sizes & Put-ups

### H-40

Sizes	Rolls/Carton	Cartons/Pallet
72mm x 375'	8	84
72mm x 450'	10	60
72mm x 500'	6	90/105
72mm x 500'	10	60
72mm x 600'	10	60

Please call our Customer Service Department for custom sizes and put-ups

While the information, data and recommendations set forth herein are believed to be accurate, Holland Manufacturing Company, Inc. makes no warranty with respect to completeness or accuracy thereto and disclaims all liability from reliance thereon. Persons utilizing this information will make their own determination as to the product's suitability for their purposes prior to use. Holland Manufacturing reserves the right to make changes to our products and related information without notice or obligation and does not warrant the accuracy or timeliness of the materials on this site and has no liability for any errors or omissions in the materials