



Product Specification

Pak-Man

Description

Pak-Man is a medium to heavy-duty grade, reinforced water activated tape. The product is available in natural and white.

Construction

Papers

Top Sheet: 30 lbs/ream Natural or 30 lbs/ream White High Strength Virgin Kraft
Bottom Sheet: 23 lbs/ream MG Natural High Strength Virgin Kraft

Laminating Adhesive

Non-Asphaltic Polypropylene based polymer
Non-Staining, Flexible, Water Resistant, Complies with FDA; CFR 175.105

Reinforcement

3-Way Fiberglass Reinforcing Pattern

Pattern: Lengthwise threads with diamond cross-machine pattern

Lengthwise Threads: H110 Fiberglass – (2-1-1-1-2) at 37/64" spacing per 3"

Cross-Machine Threads: G150 Fiberglass – Diamond Pattern 1/4" spacing between threads

Adhesive

Smooth, even coating of special high tack, water-activated, modified corn starch based adhesive

Caliper

6.5 to 8.5 mils

Performance

Tensile Data*	Machine Direction*	Cross Machine Direction*
Pak-Man Natural	60-65 lbs/in	25-30 lbs/in
Pak-Man White	60-65 lbs/in	25-30 lbs/in

*Nominal values shown.

Sizes & Put-ups

Sizes	Rolls/Carton	Cartons/Pallet
2½" x 450'	12	60
3" X 375'	8	84
3" x 450'	10	60
3" x 500'	6	90/105
3" x 500'	10	60
3" x 600'	10	60

Please call our Customer Service Department for custom sizes and put-ups

While the information, data and recommendations set forth herein are believed to be accurate, Holland Manufacturing Company, Inc. makes no warranty with respect to completeness or accuracy thereto and disclaims all liability from reliance thereon. Persons utilizing this information will make their own determination as to the product's suitability for their purposes prior to use. Holland Manufacturing reserves the right to make changes to our products and related information without notice or obligation and does not warrant the accuracy or timeliness of the materials on this site and has no liability for any errors or omissions in the materials.