



## Product Specification

# Pak-Man H-60

### Description

Pak-Man H-60 is a medium to heavy-duty grade, reinforced water activated tape. The product is available in natural and white.

### Construction

#### Papers

Top Sheet: 23 lbs/ream Natural or 30 lbs/ream White High Strength Virgin Kraft  
Bottom Sheet: 23 lbs/ream MG Natural High Strength Virgin Kraft

#### Laminating Adhesive

Non-Asphaltic Polypropylene based polymer  
Non-Staining, Flexible, Water Resistant, Complies with FDA; CFR 175.105

#### Reinforcement

3-Way Fiberglass Reinforcing Pattern

**Pattern:** Lengthwise threads with diamond cross-machine pattern

**Lengthwise Threads:** G75 Fiberglass – (2-1-1-1-2) at 7/16" spacing  
per 3"

**Cross-Machine Threads:** G150 Fiberglass – Diamond Pattern 1/4"  
spacing between threads

#### Adhesive

Smooth, even coating of special high tack, water-activated, modified corn starch based adhesive

#### Caliper

6.0 to 7.0 mils

### Performance

Tensile Data*	Machine Direction*	Cross Machine Direction*
H-60 Natural	68-76 lbs./in.	26-34 lbs./in.
H-60 White	60-65 lbs./in.	25-30 lbs./in.

\*Nominal values shown

### Sizes & Put-ups

## Pak-Man H-60

Sizes	Rolls/Carton	Cartons/Pallet
3" X 375'	8	75
3" x 450'	10	60
3" x 500'	6	90/105
3" x 500'	10	60
3" x 600'	10	60

Please call our Customer Service Department for custom sizes and put-ups

*While the information, data and recommendations set forth herein are believed to be accurate, Holland Manufacturing Company, Inc. makes no warranty with respect to completeness or accuracy thereto and disclaims all liability from reliance thereon. Persons utilizing this information will make their own determination as to the product's suitability for their purposes prior to use. Holland Manufacturing reserves the right to make changes to our products and related information without notice or obligation and does not warrant the accuracy or timeliness of the materials on this site and has no liability for any errors or omissions in the materials.*